

TAKE-UPS

SCREW TYPE AUXILIARY TAKE-UP (FOR LIVE ROLLERS)



Screw type auxiliary take-ups are the most common take-ups used on models 138VP, 196VP, 138LR, 196CALR, 196ZPA and 251CALR for additional belt take-up. Live roller model ATS4 shown at left and ATS6 shown below.



SPECIFICATIONS

4" AUX. TAKE-UP: (2) 4" dia. pulleys with 1-3/16" dia. shaft, machine crowned.

6" AUX. TAKE-UP: (2) 6" dia. pulleys with 1-7/16" dia. shaft, machine crowned.

FRAME: Depth of (4") 8" x 10 ga. formed steel, Depth of (6") 9-1/2" x 10 ga. formed steel.

TAKE-UP: 24" belt take-up.

BEARINGS: Heavy duty, relubable, ball bearings with cast iron housings.

SPECIFY MODEL NUMBER PER EXAMPLE

ATS4-33-R

ATS(pulley diameter*)-(between frames)-
(live roller type)

*Specify 4 for model ATS4 with 4" dia. pulleys or 6 for model ATS6 with 6" dia. pulleys.

MODEL ATS4 FOR LIVE ROLLERS

BF	15"	19"	21"	25"	27"	33"	39"
WT.	105	113	117	125	129	141	153

MODEL ATS6 FOR LIVE ROLLERS

BF	15"	19"	21"	25"	27"	33"	39"
WT.	119	129	135	146	151	167	183

■ 24 hour shipment ■ 2 week shipment

SCREW TYPE AUXILIARY TAKE-UP (FOR BELT CONVEYORS)



Screw type auxiliary take-ups are the most common take-ups used for models 725TB, 700SB, 700BSB, 450BOS, 796RB, 796RBF, 700SBF and 751RB for additional belt take-up. Belt conveyor model ATS4 shown at left and ATS6 shown above.



SPECIFICATIONS

4" AUX. TAKE-UP: (2) 4" dia. pulleys with 1-3/16" dia. shaft, machine crowned.

6" AUX. TAKE-UP: (2) 6" dia. pulleys with 1-7/16" dia. shaft, machine crowned.

FRAME: Depth of (4") 8" x 10 ga. formed steel, Depth of (6") 9-1/2" x 10 ga. formed steel.

TAKE-UP: 24" belt take-up.

BEARINGS: Heavy duty, relubable, ball bearings with cast iron housings.

SPECIFY MODEL NUMBER PER EXAMPLE

ATS4-21-B

ATS(pulley diameter*)-(between frames)-
(belt conveyor type**)

*Specify 4 for model ATS4 with 4" dia. pulleys or 6 for model ATS6 with 6" dia. pulleys.

**When attaching to 725TB or 450BOS, BF dimension = belt width + 1".

NOTE: 24 hour shipment on 45" and 51" BF does not include models 725TB or 450BOS.

MODEL ATS4 FOR BELT CONV.

BELT	6"	12"	18"	24"	30"	36"	42"	48"
BF	9"	15"	21"	27"	33"	39"	45"	51"
WT.	122	134	146	158	170	182	194	206

MODEL ATS6 FOR BELT CONV.

BELT	6"	12"	18"	24"	30"	36"	42"	48"
BF	9"	15"	21"	27"	33"	39"	45"	51"
WT.	132	148	164	180	196	212	228	244

■ 24 hour shipment ■ 2 week shipment

